

POWERED BY
RANGE-LITE[®]
Original



www.eliteele.com
Illuminate Your Event



HEAD OFFICE - KOLHAPUR
ELITEELECTRIC PROLIGHT Pvt. Ltd.

1847'C' Ward, Opp. Mutton Market,
Bindu Chowk, Kolhapur-416012,
Maharashtra, India.
+91231- 2644241, 2643780,
+91 9850125797, +91 8888628880,
info@eliteele.com

BRANCH- SANGLI
NEW ELITE LIGHT HOUSE

1627, Bhui Galli Corner, Khan Bhag,
Panchmukhi Maruti Road,
Sangli - 416416, Maharashtra, India
+91233-2376206
+91 9423868970, +91 9623015370
newelite1627@gmail.com

BRANCH- MUMBAI
SHREE VINAYAK ELECTRICALS

Office No. 4-5, Floor-3, 119, Maskati Mahal,
Kantilal M Sharma Marg, Lohar Chawl,
Kalbadevi, Mumbai-400002,
Maharashtra, India.
+9122-22050564,
+91 8369258669, +91 8888628880
info@eliteele.com



WE ARE ON



SINCE 1992



Product Catalog -2023

A B O U T U S

ELITEELECTRIC PROLIGHT Pvt. Ltd. formerly known as New Elite Electricals is a professional event lighting manufacturer and trader.

Our aim is to deliver competitively priced products that can cater to the demanding Indian market conditions for quality and stability while continuously supporting our customers with efficient after sales service so that they receive a profitable return on their investment.

Originally established in 1992 as a decorative lighting distributor, our intelligent lighting series has recently shot to fame in the past decade or so with some of the best event rental companies in India who have chosen our products.

Durability is our prime focus and our manufacturing process reflects this at every point. Every single product that bears our name goes through rigorous quality checks. We also conduct batch test through artificially aging randomly selected products from each batch of lights that we manufacture.

Luxury packaging and expensive promotional activities or even lower priced products are not what comes to mind when one thinks of Elite. The positive feedback that we receive from our customers is what drives us with a sense of pride and further pushes our already high standards of after sales service to new levels.



C O N T E N T S

MOVING HEAD SERIES
Page No. 04 to 09

LED MOVING HEAD SERIES
Page No. 10 to 13

STATIC LED WASH SERIES
Page No. 14 TO 19

STATIC HALOGEN WASH SERIES
Page No. 20

STROBE SERIES
Page No. 21

STATIC LED UP LIGHT SERIES
Page No. 22 TO 25

CREATIVE DISPLAY SERIES
Page No. 26 to 27

SPOT LIGHT SERIES
Page No. 28

LASER SERIES
Page No. 29 to 31

MOVING LASER SERIES
Page No. 32 to 33

EFFECT SERIES
Page No. 34 TO 37

CONTROLLER SERIES
Page No. 38 to 39

POWER DISTRIBUTION SERIES
Page No. 40

LED FLOOD LIGHTS
Page No. 41

DECORATIVE LIGHT SERIES
Page No. 42 to 43



RAINBOW 300

Rainbow 300 is the economic proposition of the current industry pinnacle of moving head beams. Drawing from its bigger brother in terms of form and function, this Fixture is a high power, multi prism discharge lamp moving head with spectacular mid air effects. This fixture utilises and Philips MSD250w lamp that help keeps it cost effective yet diversely capable. Its high precision optic lens system and Philips MSD250w lamp creates extremely high brightness with a sharp intense beam. This fixture is remarkable considering it's high output to low power consumption ratio. The unique casing enables all this in a low footprint while allowing for high speed movement with low noise.



► Model No. : 11001001

LAMP SOURCE

Lamp type: Philips MSD 250w
Average life : 1500 hours
Color temp : 8000K
Reflector: Lamp and reflector together in one unit

Lens : high precision optical lens
Beam angle : 0-4°

COLOR SYSTEM

13 color filters + Open
Rainbow can be created

GOBO SYSTEM

12 Fixed Gobos + 4 Glass Gobos
+ Open , Shake Effect.

EFFECT EQUIPMENT

Independent frost soft effect,
Mechanical linear 0-100% dimming,
Fast strobe, multiple strobe effects,
(Pulse/asynchronous/synchronous/
slow - medium - fast at random)
Prism: 2 prism wheels
(Bi-directional, Rotatable, Speed adjustable)
(1 self-rotating 8 facet circular
prism and 1 self-rotating 8+16 facet circular
prism)
Creates a total of 3 prism effects

IP RATING
IP20

MOVING PARAMETER

Angle: Pan 540°, Tilt 270°
PAN and TILT adopt an electro-optic reset system which automatically resets the parameters if any change is caused by accident.

CONTROL AND PROGRAMMING

Control channel: 16CH / 20CH
Control Mode: Standard DMX512 protocol, RDM (Optional),
Auto Run, Sound
Menu display: 16 million pixels LCD display
Menu display can be rotated 180 degrees.

ELECTRONIC CONTROL TECHNOLOGY

Intelligent fan control
Electronic sensor detection
DMX control monitor
X/Y two-phase motor drive
Query by LCD screen

POWER SUPPLY

AC100-240V 50/60Hz
Electronic ballast
Consumption : 400

PHYSICAL

Product dimensions : 25 x 32 x 54 CM
Net weight : 12.5 KG
Flight case packaging (2 in 1) : 70 x 37 x 76 CM
Gross weight : 48KG

RAINBOW 300

DISCHARGE LAMP
MOVING HEAD SERIES



DMX
CHANNEL

20CH	1CH	2CH	3CH	4CH	5CH	6CH	7CH	8CH	9CH	10CH	11CH	12CH	13CH	14CH	15CH	16CH	17CH	18CH	19CH	20CH
16CH	1CH	2CH	3CH	4CH	5CH	6CH	7CH	8CH	9CH	10CH	11CH	12CH	13CH	14CH	15CH	16CH	17CH	18CH	19CH	20CH
%	Colour Wheel	Strobe	Dimmer	Fixed Gobo	Prism	Prism Rotation	Function	Rainbow & Frost	Focus	Pan	Pan Fine	Tilt	Tilt Fine	Pan/Tilt Speed	RESET	Lamp Control	Pan/Tilt Time	Color Wheel Speed	Dimmer Speed	Gobo Speed
100%	Slow-fast rotation	Slow Strobe (1+2S flash/saw)	Slow fast pulsation	Slow + Fast rotation	Prism 3 inserted	0°-360°	EMPTY	Rainbow Wheel Inserted	↑	↔	↔	↕	↕	↕	Complete Rest in 5s	↕	↕	Fast Slow Rotation	↕	↕
75%	Color Wheel	Strobe	Dimmer	Fixed Gobo	Prism 2 inserted	0°-360°	EMPTY	Frost Wheel Inserted	↑	↔	↔	↕	↕	↕	Unused Range	Lamp On Over 3S	↕	↕	↕	↕
50%	Color Wheel	Strobe	Dimmer	Fixed Gobo	Prism 1 inserted	0°-360°	EMPTY	Rainbow Wheel Excluded	↑	↔	↔	↕	↕	↕	Unused Range	Lamp Off Over 3S	↕	↕	↕	↕
25%	Color Wheel	Strobe	Dimmer	Fixed Gobo	Prism excluded	0°-360°	EMPTY	Rainbow Wheel Excluded	↑	↔	↔	↕	↕	↕	Unused Range	Unused Range	↕	↕	↕	↕
0%	Color Wheel	Strobe	Dimmer	Fixed Gobo	Prism excluded	0°-360°	EMPTY	Rainbow Wheel Excluded	↑	↔	↔	↕	↕	↕	Unused Range	Unused Range	↕	↕	↕	↕



RAINBOW 400

DISCHARGE LAMP MOVING HEAD SERIES



MOVING HEAD SERIES

RAINBOW 400

Rainbow 400 is a high power, multi prism discharge lamp moving head with spectacular mid air effects. Its high precision optic lens system and 311w Osram lamp creates extremely high brightness with a sharp intense beam. This fixture moves from the recent tradition of measuring moving head beam brightness by checking the number that precedes the "R" of the lamp, towards an international standard of low power high efficiency lamps. The new innovative modular housing brings a modern look to moving head fixtures that is compatible with the set designs off today.



Model No. : 11001003

LAMP SOURCE

Lamp type: OSRAM 311W
 Average life : 1500 hours
 Color temp : 8000K
 Reflector: Lamp and reflector together in one unit
 Lens : High precision optical lens
 Beam angle: 2.8°

COLOR SYSTEM

14 color filters + Open
 Rainbow color effect

GOBO SYSTEM

12 Fixed Gobos + 4 Glass Gobos
 + Open , Shake Effect.

EFFECT EQUIPMENT

Independent frost soft effect,
 Mechanical linear 0-100% dimming,
 Fast strobe, multiple strobe effects,
 (Pulse/asynchronous/synchronous/
 slow - medium - fast at random)
 Prism: 2 prism wheels
 (Bi-directional, Rotatable, Speed adjustable)
 (1 self-rotating 8 facet circular
 prism and 1 self-rotating 8+16 facet circular prism)
 Creates a total of 3 prism effect

MOVING PARAMETER

Angle: Pan 540°, Tilt 270°
 PAN and TILT adopt an electro-optic
 reset system which automatically
 resets the parameters if any change
 is caused by accident.

CONTROL AND PROGRAMMING

Control channel: 16CH / 20CH
 Control Mode: Standard DMX512 protocol, RDM (Optional),
 Auto Run, Sound
 Menu display: 16 million pixels LCD display
 Menu display can be rotated 180 degrees.

ELECTRONIC CONTROL TECHNOLOGY

Intelligent fan control
 Electronic sensor detection
 DMX control monitor
 X/Y two-phase motor drive
 Query by LCD screen

POWER SUPPLY

AC100-240V 50/60Hz
 Electronic ballast
 Consumption : 500

PHYSICAL

Product dimensions: 57 x 32 x 27 CM
 Net weight: 16.5 KG
 Flight case packaging (2 in 1) : 70 x 38 x 78 CM
 Gross weight : 56KG

IP RATING

IP20

DMX CHANNEL

20CH	1CH	2CH	3CH	4CH	5CH	6CH	7CH	8CH	9CH	10CH	11CH	12CH	13CH	14CH	15CH	16CH	17CH	18CH	19CH	20CH
16CH	1CH	2CH	3CH	4CH	5CH	6CH	7CH	8CH	9CH	10CH	11CH	12CH	13CH	14CH	15CH	16CH	/	/	/	/
%	Colour Wheel	Strobe	Dimmer	Fixed Gobo	Prism	Prism 1 Rotation	Prism 2 Rotation	Rainbow & Frost	Focus	Pan	Pan Fine	Tilt	Tilt Fine	Pan/Tilt Speed	RESET	Lamp Control	Pan/Tilt Time	Color Wheel Speed	Dimmer Speed	Gobo Speed
100%	Slow-fast rotation	Slow Strobe (1+2S flash/sawc)	Stop	Slow + Fast rotation	Prism 3 inserted	0°-360°	0°-360°	Rainbow Wheel Inserted	↑	↔	↔	↕	↕	↕	Complete Rest in 5s	Lamp On Over 3S	↕	Fast Slow Rotation	↔	↔
75%	Slow-fast rotation	Slow Strobe (1+2S flash/sawc)	Stop	Fast-slow rotation	Prism 2 inserted	Slow To Fast Speed	Slow To Fast Speed	Frost Wheel Inserted	↑	↔	↔	↕	↕	↕	Unused Range	Lamp On Over 3S	↕	Max	↔	↔
50%	Slow-fast rotation	Slow Strobe (1+2S flash/sawc)	Stop	Random slow delium strobe	Prism 1 inserted	Fast To Slow Speed	Fast To Slow Speed	Rainbow Wheel Excluded	↑	↔	↔	↕	↕	↕	Unused Range	Lamp Off Over 3S	↕	Min	↔	↔
25%	Slow-fast rotation	Slow Strobe (1+2S flash/sawc)	Stop	Prism excluded	Prism excluded	Fast To Slow Speed	Fast To Slow Speed	Rainbow Wheel Excluded	↑	↔	↔	↕	↕	↕	Unused Range	Lamp Off Over 3S	↕	Min	↔	↔
0%	Slow-fast rotation	Slow Strobe (1+2S flash/sawc)	Stop	Prism excluded	Prism excluded	Fast To Slow Speed	Fast To Slow Speed	Rainbow Wheel Excluded	↑	↔	↔	↕	↕	↕	Unused Range	Lamp Off Over 3S	↕	Min	↔	↔

LCD DISPLAY | DMX 512 16/20 CH | Linkable Stand-Alone | Pre-programmed | Sound Active | WHITE | IP-20 | UHP LAMP



BSW 500

The BSW500 is a mid air effect 3 in 1 fixture that is capable of a beam, spot and wash from 1 type of light. A rugged build quality with a high end optic lens allows for these effects with no compromise. It can be used via 22 DMX channels depending on the desired functionality. It is fitted with 2 gobo wheels of which the first is static and has 11 gobos while the second is a rotating wheel with 7 changeable glass gobos and 1 open slot. The possibilities of effects that can be created with this fixture are endless.



► Model No. : 11001006

LAMP SOURCE

Lamp type: OSRAM 371W Lamp,
Average life : 2500 hours
Color temp : 8500K
Reflector: Lamp and reflector together in one unit
Lens : high precision optical lens
Beam angle: 2.5°
Zoom Range : 5°- 40° (linear High Speed zoom)

COLOR SYSTEM

8 color filters + Open
Rainbow color effect

GOBO SYSTEM

1 rotating gobo wheel with 7 glass gobo + Open, with the features of self-rotating, water running and shaking effects, gobo wheel can be positioned
1 fixed gobo wheel with 11 gobo + Open

EFFECT EQUIPMENT

Independent frost soft effect,
Mechanical linear 0-100% dimming,
Fast strobe, multiple strobe effects (pulse/asynchronous/synchronous/slow- medium-fast at random)
Prism: 2 prisms (1 self-rotating 16-facet circular prism and 1 self-rotating 6-facet linear prism) (Bi-directional, Rotatable, Speed adjustable)

MOVING PARAMETER

Angle: Pan 540°, Tilt 270°
PAN and TILT adopt an electro-optic reset system which automatically resets the parameters if any change is caused by accident.

CONTROL AND PROGRAMMING

Control channel: 22CH / 26CH
Control Mode: Standard DMX512 protocol, Auto Run, Sound.
Menu display: 16 million pixels LCD display (Touch Screen)
Menu display can be rotated 180 degrees

ELECTRONIC CONTROL TECHNOLOGY

Intelligent fan control
Electronic sensor detection
DMX control monitor
X/Y three-phase motor drive
Query by LCD screen

POWER SUPPLY

AC100-240V 50/60Hz
Electronic ballast
Consumption : 500w

PHYSICAL

Product dimensions : 39 x 285 x 64 CM
Net weight : 21.2 KG
Flight case packaging (2 in 1) : 74 x 46 x 86 CM
Gross weight : 68 KG

IP RATING

IP20

BSW 500

DISCHARGE LAMP MOVING HEAD SERIES



DMX CHANNEL

	22CH	1CH	2CH	3CH	4CH	5CH	6CH	7CH	8CH	9CH	10CH	11CH	12CH	13CH	14CH	15CH	16CH	17CH	18CH	19CH	20CH	21CH	22CH
	%	Pan	Pan Fine	Tilt	Tilt Fine	Pan/Tilt Speed	Dimmer	Strobe	Colour Wheel	Fixed Gobo	Glass Gobo	Glass Gobo Rotation	Effects Gobo	Prism 1	Prism-1 Rotation	Prism 2	Prism-2 Rotation	Zoom	Focus	Frost	CTO	Function	Control
100%																							
75%																							
50%																							
25%																							
0%																							



WASH 300

LED MOVING HEAD SERIES



DMX CHANNEL

25CH	1CH	2CH	3CH	4CH	5CH	6CH	7CH	8CH	9CH	10CH	11CH	12CH	13CH	14CH
%	Strobe	Dimmer	Zoom	Pan	Pan Fine	Tilt	Tilt Fine	RESET	Color Macro	RED	Green	Blue	White	CTO
100%	Slow Strobe (1-128 flash/row)	Dimmer	Zoom	Pan	Pan Fine	Tilt	Tilt Fine	Complete Rest in Sx	Color Macro	RED	Green	Blue	White	CTO
75%	Slow fast pulsation							Unused Range						
50%	Random Slow detum strobe													
25%														
0%									No Function					No Function

LCD DISPLAY

DMX 512 14/25/32 CH

Linkable Stand-Alone

Pre-programmed

Sound Active

WHITE

IP-20

LED LAMP



LED MOVING HEAD SERIES

WASH 300



WASH 300 is a high performance LED beam wash moving head. Extreme brightness and 8° to 54° zoom range make this fixture perfect in a range of applications, either as a beam light with multi-color rays, or as a wash light with a very wide projection. It is suitable for medium/ big venues, and it's the perfect solution for TV studios, delivering top-of-the-line visual effects or perfectly uniform wash lighting. It is equipped with 19pc 15W RGBW 4in1 LEDs.

Model No. : 11002001

LAMP SOURCE
Lamp type: 19pc 15W RGBW 4IN1 LED
Average life : 50000 hours
Lens : High quality optical lens
Beam angle: 8° - 54°

COLOR SYSTEM
RGBW 4 in 1

EFFECTS
All-optical domain dimming
High light output, low glare
Fast Strobe: 1-25HZ
Color macro and gradual color change effects

MOVING PARAMETER
Angle: Pan 540°, Tilt 270°
PAN and TILT adopt an electro-optic reset system which automatically resets the parameters if any change is caused by accident.

POWER SUPPLY
AC100-240V 50/60Hz
Switch Power
Consumption : 300W

CONTROL AND PROGRAMMING
Control Channel: 14/25/32 control channel model
Control Mode: Standard DMX512 auto run, sound.
Menu display: 16 million pixels LCD display
DMX Signal Connection: 3-pin & 5-pin XLR input/output

ELECTRONIC CONTROL TECHNOLOGY
Fixture reset is controlled through menu or light console
0-100% dimmer
Constant current drive mode
Temperature sensor, intelligently adjust light source power
DMX channel level monitoring
Fixture information query
Intelligent fan speed adjustment
Initial brightness setting for all colors
Over current, over voltage and overheating protection

PHYSICAL
Product dimensions: 42 x 31 x 47 CM
Net weight: 7.6 KG
Flight case packaging 2 in 1: 64 x 37 x 57 CM
Gross weight: 31 KG

IP RATING
IP20



POWERED BY
RANGE-LITE
Original

WASH 600

LED MOVING HEAD SERIES



19CH	1CH	2CH	3CH	4CH	5CH	6CH	7CH	8CH	9CH	10CH	11CH	12CH	13CH	14CH	15CH	16CH	17CH	18CH	19CH	20CH	21CH	22CH	23CH	24CH
%	Pan	Pan Fine	Tilt	Tilt Fine	Pan/Tilt Speed	Zoom	Dimmer	Strobe	RED	Green	Blue	White	CTO	Function	Function 1	Function 2	BACK RED	BACK Green	BACK Blue	BACK White	Function	Function Speed	Function	RESET
100%																								
75%																								
50%																								
25%																								
0%																								

DMX CHANNEL

- LCD DISPLAY
- DMX 512 24/36/48CH
- Linkable Stand-Alone
- Pre-programmed
- Sound Active
- WHITE
- IP-20
- LED LAMP



LED MOVING HEAD SERIES

WASH 600



This "Big boy's" moving head wash is suited for larger stage sets and festival level applications. With a variable zoom angle of 8 degrees to 45 degrees, it is capable of a beam and wash effect. Its 24, 36 and 48 channel control options, makes it suitable for a large range of applications. The fixture comprises of 37pcs of 15w 4in1 RGBW led bulbs that are capable of a 50,000 hour lamp life.

Model No. : 11002003

LAMP SOURCE
 Lamp type: 37pc 15W RGBW LED
 Average life : 50000 hours
 Lens : Optical lens
 Beam angle: 8° - 45°

COLOR SYSTEM
 RGBW 4 in 1

EFFECTS
 All-optical domain dimming,
 65536 grade dimming accuracy
 High light output, low glare
 Fast strobe: 1-25Hz
 Color macro and gradual color change effects

MOVING PARAMETER
 Angle: Pan 540°, Tilt 270°
 PAN and TILT adopt an electro-optic reset system which automatically resets the parameters if any change is caused by accident.

POWER SUPPLY
 AC100-240V 50/60Hz
 Switch Power
 Consumption : 500w

CONTROL AND PROGRAMMING
 Control Channel: 24/36/48 control channel model
 Control Mode: Standard DMX512
 Auto run, sound.
 Menu display: 16 million pixels LCD display
 Menu display can be rotated 180 degrees
 DMX Signal Connection: 3 & 5 pin XLR input/output

ELECTRONIC CONTROL TECHNOLOGY
 Fixture reset is controlled through menu or light console
 0-100% dimmer
 Constant current drive mode
 Temperature sensor, intelligently adjust the light source power
 DMX channel level monitoring
 Fixture information query
 Intelligent fan speed adjustment
 Initial brightness setting for all colors

PHYSICAL
 Product dimensions: 27 x 38 x 48 CM
 Net weight: 12.7 KG
 Flight case packaging 2 in 1: 74 x 45 x 65 CM
 Gross weight: 45 KG

IP RATING
 IP20



▶ Model No. : 11003001



PAR 300 RGBW IP

This waterproof LED PAR with its 60X3W RGBW LEDs, The all New Design die-cast aluminum housing and super resistant heat sink ensures that the fixture delivers maximum performance with rugged usability while drawing minimal power. The fixture can be ordered with 5 different lens angle options.

Voltage: AC115-230V, 50/60 Hz
Power: 200W
Lamp source : 60X3W RGBW / RGB+WW / RGB+UV
Color temperature : 6000K
Life time : 80000h
Lens angle : 15/25/20/45/60°
Channel : 4/8CH
Control mode : DMX512, master-slave, auto, sound control
IP Rating : IP65
Net Weight : 6.40 KG
Gross Weight: 14.4 KG (Cardboard packing 2in1)
Package : 60X30X33 CM (Cardboard packing 2in1)

▶ Model No. : 11003002



PAR 200 RGBW IP

This waterproof LED PAR with its 54X3W RGBW LEDs, die-cast aluminum housing and super resistant heat sink ensures that the fixture delivers maximum performance with rugged usability while drawing minimal power. The slim body provides all the necessary features in a small housing. The fixture can be ordered with 5 different lens angle options.

Voltage : AC115-230V, 50/60 Hz
Power : 200W
Lamp source: 54X3W RGBW
Color temperature : 6000K
Life time : 80000h
Lens angle : 15/25/20/45/60 °
Channel : 4/8 CH
Control mode: DMX512, master-slave, auto, sound control
IP Rating : IP65
Net Weight : 5.5 KG
Gross Weight : 12.6 KG (Cardboard packing 2in1)
Package : 60X30X33 CM (Cardboard packing 2in1)

▶ Model No. : 11003003



PAR 300 RGBW

This LED PAR with its 60X3W RGBW LEDs, The all new design die-cast aluminum housing and super resistant heat sink ensures that the fixture delivers maximum performance with rugged usability while drawing minimal power. The fixture can be ordered with 5 different lens angle options.

Voltage : AC115-230V, 50/60 Hz
Power : 200W
Lamp source: 60X3W RGBW / RGB+WW / RGB+UV
Color temperature: 6000K
Life time: 80000h
Lens angle : 15/25/20/45/60 °
Channel: 4/8CH
Control mode: DMX512, master-slave, auto, sound control
IP Rating: IP20
Net Weight : 3.65 KG
Gross Weight: 17 KG (Cardboard packing 4in1)
Package: 56X56X32 CM (Cardboard packing 4in1)

▶ Model No. : 11003004



PAR 200 RGBW

This LED PAR with its 54X3W RGBW LEDs, die-cast aluminum housing and super resistant heat sink ensures that the fixture delivers maximum performance with rugged usability while drawing minimal power. The fixture can be ordered with 5 different lens angle options.

Voltage : AC115-230V, 50/60 Hz
Power : 200W
Lamp source: 54X3W
Color temperature: 6000K
Life time: 80000h
Lens angle : 15/25/20/45/60 °
Channel: 8CH
Control mode: DMX512, master-slave, auto, sound control
IP Rating: IP20
Net Weight : 3.7 KG
Gross Weight: 17.7 KG (Cardboard packing 4in1)
Package: 53X53X39 CM (Cardboard packing 4in1)



▶ Model No. : 11003005

PAR 160 RGB

This LED PAR with its 60X3W tricolor RGB LEDs, die-cast aluminum housing and super resistant heat sink ensures that the fixture delivers maximum performance with rugged usability while drawing minimal power. The slim body provides all the necessary features in a small housing. The fixture can be ordered with 5 different lens angle options.

Voltage : AC90-240V, 50 / 60Hz
 Total power : 120W
 Light Source : 60X3W 3in1
 Color temperature : 6000K
 Life time : 80000h
 Lens angle : 15/25/20/45/60 degree (customizable)
 Channel : 4/8 CH
 Control Mode : DMX512, auto, master-slave, sound control
 IP Rating : IP 20
 Net Weight : 3 KG
 Gross Weight : 13.1 KG (Cardboard packing 4in1)
 Package : 48X48X25 CM (Cardboard packing 4in1)

▶ Model No. : 11003006

PAR 150 RGB

This LED PAR with its 54X3W tricolor RGB LEDs, die-cast aluminum housing and super resistant heat sink ensures that the fixture delivers maximum performance with rugged usability while drawing minimal power. The slim body provides all the necessary features in a small housing. The fixture can be ordered with 5 different lens angle options.

Voltage: AC90-240V, 50 / 60Hz
 Total power: 120W
 Light Source: 54X3W 3in1
 Color temperature: 6000K
 Life time: 80000h
 Lens angle: 15/25/20/45/60 degree (customizable)
 Channel: 8 CH
 Control Mode: DMX512, auto, master-slave, sound control
 Waterproof rating: IP 20
 Net Weight : 2.6 KG
 Gross Weight: 12.1 KG (Cardboard packing 4in1)
 Package: 49X49X28 CM (Cardboard packing 4in1)

▶ Model No. : 11003007

PAR 300 WW IP

This waterproof LED PAR with its 60X3W warm white LEDs, The all new design die-cast aluminum housing and super resistant heat sink ensures that the fixture delivers maximum performance with rugged usability while drawing minimal power. Aimed at being a PAR 64 substitute, the fixture can be ordered with 5 different lens angle options.

Voltage : AC115-230V, 50/60 Hz
 Power : 200W
 Lamp source: 60X3W WW
 Color temperature: 2800/3000/3200k
 Life time : 80000h
 Lens angle : 25°
 Channel : 2 OR 4/8 CH
 Control mode : DMX512, master-slave, auto, sound control
 IP Rating : IP65
 Net Weight : 6.40 KG
 Gross Weight : 14.4 KG (Cardboard packing 2in1)
 Package : 60X30X33 CM (Cardboard packing 2in1)

▶ Model No. : 11003008

PAR 300 WW

This waterproof LED PAR with its 60X3W warm white LEDs, the all new design die-cast aluminum housing and super resistant heat sink ensures that the fixture delivers maximum performance with rugged usability while drawing minimal power. Aimed at being a PAR 64 substitute, the fixture can be ordered with 5 different lens angle options.

Voltage : AC115-230V, 50/60 Hz
 Power : 200W
 Lamp source: 60X3W WW
 Color temperature: 2800/3000/3200k
 Life time : 80000h
 Lens angle : 15/25/20/45/60 °
 Channel : 2 OR 4/8 CH
 Control mode : DMX512, master-slave, auto, sound control
 IP Rating : IP65
 Net Weight : 3.65 KG
 Gross Weight : 17 KG (Cardboard packing 2in1)
 Package : 56X56X32 CM (Cardboard packing 2in1)



▶ Model No. : 11003010

**PAR 200 COB WW
PAR 200 COB White + WW**

This fixture aims to completely replace PAR 64 cans once and for all. With its colour matched 4 lamps of 50w each in a die cast aluminium housing it is a modern, more rugged power efficient swap for the traditional face light fixtures.

Voltage : AC115-230V, 50/60 Hz
 Power : 200W
 Lamp source: 4X50W WW OR
 2X50W White + 2X50W WW
 Color temperature: 3200K
 Life time: 80000h
 Lens angle : 15/25 °
 Channel: 4/8CH
 Control mode: DMX512, master-slave, auto, sound control
 IP Rating: IP20
 Net Weight : 3.65 KG
 Gross Weight: 17 KG (Cardboard packing 4in1)
 Package: 56X56X32 CM (Cardboard packing 4in1)

▶ Model No. : 11003009

PAR 160 WW

This waterproof LED PAR with its 60X3 WW LEDs give you unparalleled light output and seamless color mixing, With Drawing very low power consumption, With die-cast aluminum, super well heat sink to assure a long life time for LEDs.

Voltage : AC90-240V, 50 / 60Hz
 Total power : 150W
 Light Source :60X3W
 Color temperature : 2800/3000/3200k
 Life time : 80000h
 Lens angle : 15/25/20/45/60 degree (customizable)
 Channel : 2 CH
 Control Mode : DMX512, auto, master-slave, sound control
 IP Rating : IP 20
 Net Weight : 3 KG
 Gross Weight : 13.1 KG (Cardboard packing 4in1)
 Package : 48X48X25 CM (Cardboard packing 4in1)

▶ Model No. : 11003011

BLINDER 400 WW

This 4-way blinder is equipped with 4pcs of 100W warm white LED lamps. It has ultra-smooth, fine dimming capabilities and can be run on 4 modes using 1, 2, 4 or 8 DMX channels.

Power supply voltage : AC90V-240V, 50/60Hz;
 Rated power : 450W
 Source : COB 100W
 Lamp quantity : 4
 Color temperature : 2800K/3000K/3200K
 Channel mode : 1/2/4/8CH
 Control mode : DMX512 control and manual adjustment
 Signal : international standard DMX512 signal (3 core interface)
 Other functions : display screen saver
 0%-100% linear dimming No flicker
 Fan control (low speed slow ,air cooling)
 Body material : Iron shell protection
 IP Rating : IP20
 Net Weight : 10.2 KG
 Flight case packaging (2 in 1) : 47 X 40 X 57 CM
 Gross Weight : 19 KG

▶ Model No. : 11003012

BLINDER 200 WW

This 2-way blinder is equipped with 2pcs of 100W warm white LED lamps. It has ultra-smooth, fine dimming capabilities and can be run on 2 modes using 2 or 6 DMX channels.

Power supply voltage : AC90V-240V, 50/60Hz;
 Rated power : 220W
 Source : COB 100W
 Lamp quantity : 2
 Color temperature : 2800/3000/3200K
 Channel mode : 1/2/6CH
 Control mode : DMX512 control and manual adjustment
 Signal : international standard DMX512 signal (3 core interface)
 Other functions : display screen saver
 0%-100% linear dimming No flicker
 Fan control (low speed, slow, air cooling)
 Body material : iron shell protection
 IP Rating : IP20
 Net Weight : 5.1 KG
 Flight case packaging (2 in 1) : 43 X 43 X 26 CM
 Gross Weight : 18.8 KG



▶ Model No. : 11004001

HALOGEN BLINDER

This halogen based molefay is a 4-way unit with 650W halogen sealed bulbs each.

Voltage : 220v / 50Hz
 Power : 2600 W
 Lamp source: Par 36 120v / 650w / quartz halogen sealed Bulb
 Color temperature; 3200K
 Size : 40*41*15 CM
 Weight : 3.9 KG (Only housing without lamp)
 Flight case packaging (4 in 1) : 73 X 51 X 58 CM
 Gross Weight : 36.48 KG

▶ Model No. : 11004003

HALOGEN PAR

The traditional, all-time favorite parabolic aluminum reflector fixture in its well know PAR 64 and PAR 36 format.

Voltage : 220v / 50Hz
 Power : 1000W / 650 W
 Lamp source : PAR61 1000W / 650W halogen sealed Bulb
 Color temperature; 3200K
 IP Rating : IP 20
 Net Weight : 2.1 KG

▶ Model No. : 11005001

STROBE 1000 RGB

The new high-powered LED strobe that uses 1000 pcs of RGB LED lamps can create an output of 80,000 lumens at a 120-degree angle. It can be used with either the high or low power mode and draws a maximum of 450W. The unit has a built in multi voltage auto switching power supply.

Rated voltage : AC110-220V ±10%/50-60HZ
 Rated power : 450W
 Chassis : full aluminum
 Emitting color : RGB
 Light source life : More than 50,000 hours
 A lamp number : 1000pc 5054 LED
 Dimming : 0-100% linear electronic dimming
 Strobe : 1 -30 times / second conventional random strobe, flash, flash array
 Control mode : DMX512, master / slave mode, voice mode, single mode, self-propelled
 Channel function : dimmer, strobe, red, green, blue, macro, macro speed, Auto
 Channel : 16/6 CH
 Appearance : metal shell, streamline design
 Net weight : 7.6 KG
 Gross weight : 17.5 KG
 Cardboard packing (2in1)
 Carton size : 56 X 34 X 44 CM

▶ Model No. : 11005003

STROBE 1000 PIXEL

The new high-powered LED strobe that uses 1000 pcs of RGB LED lamps can create an output of 80,000 lumens at a 120-degree angle. It can be used with either the high or low power mode and draws a maximum of 450W. The new strobe have 112 pixel section which creates amazing pixel effects the unit has a built in multi voltage auto switching power supply.

Rated voltage : AC110-220V ±10%/50-60HZ
 Rated power : 450W
 Chassis : full aluminum
 Emitting color : RGB
 Light source life : More than 50,000 hours
 A lamp number : 1000pc 5054 LED
 Dimming : 0-100% linear electronic dimming
 Strobe : 1 -30 times / second conventional random strobe, flash, flash array
 Control mode : DMX512, master / slave mode, voice mode, single mode, self-propelled
 Channel function : dimmer, strobe, red, green, blue, macro, macro speed, Auto
 Channel : 3/11/36 CH
 Appearance : metal shell, streamline design
 Net weight : 7.6 KG
 Gross weight : 17.5 KG
 Cardboard packing (2in1)
 Carton size : 56 X 34 X 44 CM



▶ Model No. : 11006003

WALL WASH 600

This dual application fixture can be used as a wall wash as well as a sleek strobe mounted on the back line or pillars of a truss. The optics comprise of 192pcs of 3W led that are oriented in a 12 section array. These arrays can be individually controlled to enable pre programmed or custom chase sequences

Beam angle : 40°
DMX channels : 5/11/17/ CH
Control mode : DMX512
master-slave, sound control
Display control : auto run mode, Master/slave
Dimmer : linear or non linear
Dimmer 0-100%
LED Qty : 192 x 3W RGB WW
Voltage : 180-264V
Total Power : 600W
Overheat protection :
Net Weight : 8.5KG
Package : 101 X 31 X 40 CM
Flight case packaging (2 in 1)
Gross Weight : 33 KG
IP Rating : IP 20



▶ Model No. : 11006002

WALL WASH 200 IP

This waterproof fixture contains 1 row of 18 RGBW quad color LED lamps make it ideal for up lighting where stealth is necessary. Each LED can be individually controlled or "Pixel Mapped".

Beam angle : 15°/25°/45°
DMX channels : 9/23/72 CH
Control mode : DMX512
master-slave, sound control
Display control : auto run mode, Master/slave
Dimmer : linear or non linear
dimmer 0-100%
LED Qty : 14 x 30W 4in1 LED
Voltage : 180-264V
Total Power : 260W
Overheat protection :
Net Weight : 7.3 KG
Flight case packaging (2 in 1) : 107 X 27 X 24CM
Gross Weight : 24 KG
IP Rating : IP65



▶ Model No. : 11006005

WALL WASH 250

A fixture that contains 1 row of 40 RGB 3in1 LED lamps it is ideal for traditional up lighting .The optics comprise of 40pcs of 3W led that are oriented in a 40 section array. These arrays can be individually controlled to enable pre programmed or custom chase sequences

Lamp Power : 120W
Voltage : AC90-250V, 50-60Hz
LED Qty : 40 x 3W
Color : RGB 3 in 1
Life time : 60000h
Control mode : auto run mode, Master/slave
Optics : 3°
IP Rating : IP20
Operation Temperature : -20°C-45°C
Material : MS body
Control signal : DMX512
Channels : 3/4/6/7/8/12/13/24/25/60/61/120/121CH
Dimmer : linear or non linear
dimmer 0-100%
Strobe : 0-25Hz/sec
Net Weight : 2.2 KG
Gross Weight : 10 KG
Package : 105X10.6X15.5CM
Flight case packing (2in1)



▶ Model No. : 11006004

WALL WASH 150

A fixture that contains 2 rows of 32 RGB 3in1 LED lamps it is ideal for traditional up lighting.The optics comprise of 64pcs of 3W led that are oriented in a 8 section array. These arrays can be individually controlled to enable pre programmed or custom chase sequences

Lamp Power : 200W
Voltage : AC90-250V, 50-60Hz
LED Qty : 64 x 3W
Color : RGB 3in1
Life time : 50000h
Control mode : auto run mode, Master/slave
Optics : 25°
IP Rating : IP20
Operation Temperature : -20°C-45°C
Control signal : DMX512
Channels : 2/3/4/7/14/26CH
Dimmer : linear or non linear
dimmer 0-100%
Strobe : 0-25Hz/sec
Net Weight : 3.1 KG
Gross Weight : 8 KG
Package : 108X23X14 CM
Cardboard packing (2in1)





PIXEL BAR CLEAR

GLASS COVER
The glass panels will not suffer from the usual problems of the silicon based outdoor led strip.

RGB
MORE STABLE

BLACK / WHITE TYPE RGB / SINGLE COLOR
Have different color lighting from the same addressable led of the building facade.

FW1935 INDEPENDENT IC

PURE COPPER

CLIP-INSTALL
Easiest way to use this led strip.

AUTO ADDRESSING

▶ Model No. : 11016001

▶ Model No. : 11016002

NAME	PIXEL BAR CLEAR 1000	PIXEL BAR CLEAR 500
MODEL NO	11016001	11016002
LED LAMP QTY	48LED LAMP 5050	24LED LAMP 5050
PIXEL	8 PIXEL / 16 PIXEL	4 PIXEL / 8 PIXEL
LED BRAND	OSRAM / EPISTAR	OSRAM / EPISTAR
INPUT VOLTAGE	DC24V / DC12V	DC24V / DC12V
POWER CONSUMPTION	10W	5W
BRIGHTNESS	500Lm	500Lm
DIMENSION	28*25*1000mm	28*25*500mm
IP RATING	IP66	IP66
CRUST MATERIAL	ALUMINUM + GLASS	ALUMINUM + GLASS
INSTALLATION WAY	CLIP	CLIP
SIGNAL TYPE	SPI Ws2811 / Fw1935	SPI Ws2811 / FW1935
BODY COLOR	GREY / SILVER	GREY / SILVER
VIEW ANGEL	120 DEGREE	120 DEGREE

PIXEL BAR MILKY

ACRYLIC COVER
Have better mixing color effect through the acrylic milky white cover.

RGB
RGBW
SINGLE COLOR

FW1935 INDEPENDENT IC

GOOD QUALITY EPISTAR / OSRAM CHIP

ACRYLIC END CAP CONNECTION PERFECT

ALUMINUM ALLOY

AUTO ADDRESSING

▶ Model No. : 11016003

▶ Model No. : 11016004

NAME	PIXEL BAR MILKY 1000	PIXEL BAR MILKY 500
MODEL NO	11016003	11016004
LED LAMP QTY	48LED LAMP 5050	24LED LAMP 5050
PIXEL	8 PIXEL / 16 PIXEL	4 PIXEL / 8 PIXEL
LED BRAND	OSRAM / EPISTAR	OSRAM / EPISTAR
INPUT VOLTAGE	DC24V / DC12V	DC24V / DC12V
POWER CONSUMPTION	10W	10W
BRIGHTNESS	500Lm	500Lm
DIMENSION	30*45*1000mm	30*45*500mm
IP RATING	IP68	IP68
CRUST MATERIAL	ALUMINUM	ALUMINUM
INSTALLATION WAY	CLIP	CLIP
SIGNAL TYPE	SPI Ws2811 / FW1935	SPI Ws2811 // Fw1935
BODY COLOR	GREY / SILVER	GREY / SILVER
VIEW ANGEL	180 DEGREE	180 DEGREE





Professional Display Solution

Excellent visual experiences to fulfill your advertising requirements or more applications. PWM high refresh rate driving IC ensures a first-class gray scale even in low brightness.

Model Name	P3.84 INDOOR DISPLAY	P3.84 OUTDOOR LED DISPLAY	P4.81 INDOOR LED DISPLAY	P4.81 OUTDOOR LED DISPLAY
Model No.:				
01 Screen resolution	562500 Pixels		360000 Pixels	
02 LED BRANDLED	HONG SHENG	KING LIGHT	HONG SHENG	KING LIGHT
03 LAMP MODEL	SMD 2020	SMD 1921	SMD 2020	SMD 1921
04 LED Configuration	1R1G1B			
05 Pixel Pitch	3.84 mm		4.81 mm	
06 Physical Density	67817 PIXEL/ M2		43403 PIXEL/M2	
07 Module Size	288 x 288 mm			
08 Module Resolution	75 X 75 Dots		75 X 75 Dots	
09 Drive Mode	1/255	1/155	1/155	1/155
10 Cabinet Configuration	576mm X 576 mm X 85mm			
11 Cabinet Resolution	150 X 150 Dots		120 X 120 Dots	
12 Cabinet Weight	9.8 Kgs			
13 Module QuANTITY	4 pcs			
14 Material of Cabinet	Die cast aluminum alloy			
15 Color of Cabinet	Black (can be changed free)			
16 Brightness	≥800 cd/m2	≥4000 cd/m2	≥800 cd/m2	≥4000 cd/m2
17 View Angle	120°(h),110° (v)			
18 Minimum View Distance	3.-100m			
19 Gray Scale	≥16bits/ 4096 level			
20 Color Capacity	1.67billion			
21 Maximum Power Consumption	500 W/m2	500 W/m2	500 W/m2	500 W/m2
22 Average Power Consumption	180/m2	200/m2	180/m2	200/m2
23 Operating Power Source	220V,50-60Hz			
24 recieving card	NOVA STAR , A55-N			
25 power supply brand	rongtronic			
26 Refresh Rate	≥3840 Hz			
27 DRIVE IC	SM 16380	ICN 2153	SM 16380	ICN 3153 / SM 16380
28 SERVICE	FRONT OR REAR	REAR	FORNT / REAR	REAR
29 MODULE CAONNECTION	SOLID CONNECTION			
30 Control Mode	Synchronous with PC			
31 Control Distance	UTP CAT5E:100m,Multi-Mode Fiber:500m,Single-Mode Fiber:15km			
32 Stock Temperature	(-40°C ~ +85°C)			
33 Working Temperature	(-20°C ~ +50°C)			
34 Operating Humidity	10-90 % RH			
35 Protection Rating	IP 31 INDOOR	IP65	IP 31	IP65
36 Flight Case Packaging (4 in 1)	66 X 49 X 80			
37 Gross Weight	61 Kg			



▶ Model No. : 11007003

FOLLOW SPOT 7R

Power consumption : 450W
 Bulb specification : OSRAM 7R
 Color : 4 colors + white,
 Control signal : self-matching signal
 Control mode : Stand-alone mode
 Optical system : high precision (4 fans)
 Thermal system : high-strength air-cooled (double fan)
 Aperture effect : adjustable aperture size
 Strobe : 1-7 times / second strobe
 Color temperature : 5600K,/6000K/3200K
 Light Distance : 10-25M
 Light angle : 23°
 Safety measures : meet a variety of safety standards,
 IP20 protection level, the power cord in line with CE20 /
 22 three standard, high temperature automatic cut off
 protection device
 Shell : Aluminum alloy edge
 Net Weight: 12.3 KG
 Gross Weight : 28.4 (Flight Case)
 Size : 68 X 44 X 42 CM

▶ Model No. : 11007001

PROFILE SPOT LED

The custom engineered 200W LED fixture is a true replacement for tradition tungsten lamp profiles spots. With its clean, cut lines and variable focus, it is ideal for theater and rental applications. It is available with 4 different degree options to select from.

200W LED profile spot
 Lamp Power : 200W
 Total power : 250W
 Voltage : AC100V-250V/50Hz/60Hz
 Color temperature : 3200K, 5600K
 Control signal : DMX512
 Lamp : pure white, warm white.
 Point of view : the volume is relatively small, relatively high quality of the optical system can choose different lenses (19° /26° /36° to 50°)
 Channel mode : 2 CH
 Size: 70*30*32 CM
 Gross weight: 8.4 KG
 Net weight: 7 KG

▶ Model No. : 11008019

LASER BATTEN RGB 12000/18000

A six head Laser Batten is a professional full color laser with full X/Y scanning with ILDA and DMX control. Perfect for large indoor events with single beam projection and creating great stage effects for nearly any size of venue when utilising the in-built pre-set patterns.

Voltage : AC115-230V, 50/60 Hz
 Laser Power : 3W X 6
 Lamp source: RED : 700MW/638nm
 GREEN : 1W/525nm
 BLUE : 1.4W/450nm
 Scanner : 20K
 Max angle : 50°

Control mode : ILDA,DMX512, master-slave,auto, sound control
 IP Rating : Ip20
 Size : 73X21X19 CM
 Net Weight : 18.5 KG
 Gross Weight : 63.20 KG (Flight case packaging 2 in 1)
 Package : 39X55X79 CM (Flight case packaging 2 in 1)

▶ Model No. : 11008018

LASER BATTEN RED 3000

A 6 head aperture laser system with single red beam outputs and DMX control. Suitable for medium to large-sized events and great for creating stage effects.

Voltage : AC115-230V, 50/60 Hz
 Laser Power : 500MW X 6
 Lamp source: RED : 500MW/638nm
 Control mode : DMX512, master-slave,auto, sound control

IP Rating : Ip20
 Size : 85X24X10 CM
 Net Weight :10.2 KG
 Gross Weight : 36.09 KG (Flight case packaging 2 in 1)
 Package : 103X42X32 CM (Flight case packaging 2 in 1)



BIG POWER LASER SERIES LASER SERIES



LASER SERIES

GREEN

POWER OF OUTPUT	2W	3W	5W	12W	15W	20W	30W
MODEL NO	11008001	11008002	11008003	11008004	11008005	11008006	11008007
POWER / WAVELENGTH	GREEN 2W / 520nm	GREEN 3W / 520nm	GREEN 5W / 520nm	GREEN 12W / 520nm	GREEN 15W / 520nm	GREEN 20W / 520nm	GREEN 30W / 520nm
CONTROL MODE	DMX512,Auto,Sound,ILDA in/out, SD.128 patterns, X/Y axis, power knobs						
SCANNER SYSTEM	High speed scanner, Max scan angle: 60 degree, Max speed: 40K						
PROGRAM EFFECT	Many beams, graphics, blanking, inside 128 patterns						
POWERAC	"110/220V 50/60HZ						
SIZE (CM)	31 X 30 X 38	31 X 30 X 38	38 X 30 X 48	52 X 59 X 58	52 X 59 X 58	52 X 59 X 58	52 X 59 X 58
WEIGHT (KG)	NW 6.5KG / GW 11.5 KG	NW 6.5KG / GW 11.5 KG	NW14.5KG /GW 22.6 KG	NW 27.7 KG /GW 51.8 KG	NW 27.7 KG /GW 51.8 KG	NW 48KG /GW 72KG	NW 48KG /GW 72KG
APPLICABLE PLACES	Club, wedding, party, big shows, outdoor skymark, theme park.						



RGB

POWER OF OUTPUT	3W	5W	10W	12W	15W	20W	40W
MODEL NO	11008010	11008009	11008011	11008030	11008012	11008013	11008015
POWER / WAVELENGTH	RED 0.5W/638nm	RED 1W/638nm	RED 3W/638nm	RED 3.5 W/638nm	RED 4W/638nm	RED 6W/638nm	RED 14W/638nm
POWER / WAVELENGTH	GREEN 1W / 520nm	GREEN 2W / 520nm	GREEN 3W / 520nm	GREEN 4.5 W/520nm	GREEN 5W/ 520nm	GREEN 6W / 520nm	GREEN 16W / 520nm
POWER / WAVELENGTH	BLUE 1.8W / 445nm	BLUE 2W / 445nm	BLUE 4W / 445nm	BLUE 4 W/ 445nm	BLUE 6W/445nm	BLUE 8W / 445nm	BLUE 16W / 445nm
CONTROL MODE	DMX512,Auto,Sound,ILDA in/out, SD.128 patterns, X/Y axis, power knobs						
SCANNER SYSTEM	High speed scanner, Max scan angle: 60 degree, Max speed: 40K						
PROGRAM EFFECT	Many beams, graphics, blanking, inside 128 patterns						
POWER	AC"110/220V 50/60HZ						
SIZE (CM)	31 X 30 X 38	38 X 30 X 48	49 X 43 X 37	49 X 43 X 37	42 X 54 X 42	42 X 54 X 42	48 X 29 X 46
WEIGHT (KG)	NW 6.5KG / GW 11.5 KG	NW 14.5KG / GW 22.6KG	NW 14 KG / GW 22.74 KG	NW 14 KG / GW 22.74 KG	NW 21.1 KG / GW 42 KG	NW 35.80KG / GW48KG	NW 46KG / GW 55KG
APPLICABLE PLACES	Club, wedding, party, big shows, outdoor skymark, theme park.						

POWERED BY
RANGE-LITE
Original

LCD
DISPLAY

DMX 512
24/36/48CH

Linkable
Stand-Alone

Pre-programmed

Sound Active

IP • 20



MOVING LASER SERIES



MOVING LASER SERIES



- Rated voltage: AC100~240V 50/60Hz
- Power consumption: ≤100W
- Scanner: 25kpps, scan angle: max±30°; Input signal: ±5V; Linearity distortion < 2%
- Motor: 3 phase 42 motor 2pcs
- X axis 540° rotation, Y axis 270° rotation
- Modulation: analog
- Beam diameter and divergence: 3*6.5mm; 1.5mrad
- Control mode: music (black out)/ automatic/master-slave/DMX512(6/40CH)/ILDA
- Control interface: 3 pin DMX512/25DB ILDA
- Demonstration effect: built-in 140 pattern and 5 pages of animation
- DMX effect: single pattern mode, and with the function of unique blanking, strobe, rotation, movement, billowing, zoom, write in, speed and color etc.
- Operating requirement: dry, less dust, 0~35°C (environmental temperature), will reduce the attenuation of the diode and extend the life of the light.
- Application: disco, club, concert, medium indoor venue, festival

	RGB					
POWER OF OUTPUT	2W	3W	4W	6W	10W	12W
MODEL NO	11015001	11015002	11015003	11015004	11015005	11015006
POWER / WAVELENGTH	RED 635-500MW	RED 635-700MW	RED 635-1W	RED 635-1.6W	RED 635-3W	RED 635-4W
POWER / WAVELENGTH	GREEN 525-500MW	GREEN 525-900MW	GREEN 525-1W	GREEN 525-1.6W	GREEN 525-3W	GREEN 525-4W
POWER / WAVELENGTH	BLUE 450-1W	BLUE 450-1.5W	BLUE 450-2W	BLUE 450-3W	BLUE 450-4W	BLUE 450-4W
SIZE (CM)	34.5 X 23 X 48	34.5 X 23 X 48	34.5 X 23 X 48	52 X 41 X 70	52 X 41 X 70	52 X 41 X 70
WEIGHT (KG)	9.5 kg	9.5 kg	9.5 kg	21.2 kg	21.2 kg	21.2 kg

- LCD DISPLAY
- DMX 512 24/36/48CH
- Linkable Stand-Alone
- Pre-programmed
- Sound Active
- WHITE
- IP-20



▶ Model No.: 11010001

FOG 500

The FOG 500 is capable of small smoke at a low cost. It is ideally suited for smaller stage shows and is durable and easy to used. It comes equipped with a manual controlled as well as a remote.

Heat up time : 6 M
 Controller : remote controller, manual controller
 Electronic thermo switch
 Output : 6400 cu.ft / M
 Fluid consumption rate : 32 M / L (100% output)
 Tank capacity : 0.5 L
 Power : AC110V, 220V-250V 50-60Hz
 Heater : 500 W
 New Weight : 1.5 KG
 Gross Weight: 19.75 KG
 Package : 82X28X35 CM
 Cardboard packing (4in1)

▶ Model No.: 11010002

FOG 1500

The FOG 1500 is capable of big smoke at a low cost. It is ideally suited for smaller stage shows and is durable and easy to used. It comes equipped with a manual controlled as well as a remote. It uses a microcomputer temperature regulator instead of cheap and dangerous mechanical temperature control units.

Heat up time : 3 M
 Controller : DMX 512, remote controller, manual controller
 Electronic thermo switch
 Output : 16000 cu.ft / M
 Fluid consumption rate : 14 M / L (100% output)
 Tank capacity : 2.5 L
 Smoke Distance : 5 mtr.
 Voltage Power : AC110V, 220V-250V 50-60Hz
 Heater : 1500 W
 New Weight : 5.1 KG Gross Weight: 6.65 KG
 Dimensions: 51x24x30 CM

▶ Model No.: 11010003

FOG VERTICAL 1500

FOG VERTICAL 1500 is a vertical fog machine that is suitable for high-end indoor and outdoor applications. It can either be placed flat on the floor, mounted on a wall or hung from brackets. The jets displace the fog up to 6 meters in height.

Manual controller.
 Heat up time : 5 M
 Controller : Remote controller, DMX512, Manual controller
 Electronic thermo switch
 Output : 18000 cu.ft/M
 Fluid consumption rate : 6.7 M / L (100% output)
 Tank capacity : 2.5 L
 Smoke Distance : 6.8 Mtr.
 Power : AC110V , 220V-250V 50-60Hz
 Heater : 1500 W New Weight : 6.5 KG
 Gross Weight : 7.6 KG Dimensions : 47x38x27 CM

▶ Model No.: 11010004

FOG 3000

This massive output fog machine will satisfy the most demanding expectations. Its dependability combined with its high output makes the envy of other fog machines. A new pro grade atomizer has been fitted on the unit.

Heat up time : 3 M
 Controller : remote controller, DMX512, manual controller
 Electronic thermo switch
 Output : 30000 cu.ft/M
 Fluid consumption rate : 5.7 M / L (100% output)
 Tank capacity : 5 L
 Power : AC110V , 220V-250V 50-60Hz
 Heater : 3000 W
 Weight : 13.2 KG
 Dimensions : 44x38x29 CM

▶ Model No.: 11010005

HAZE 2000

The DJ-2000 haze machine comes fitted in a standard aluminum flight case that allows these units to be stacked on top of each other. It features a unique heating system that allows it to produce continuous even haze while remaining free from clogging. This in turn results in reduced maintenance and down time.

Its low operating noise level makes it an ideal choice for sensitive environments including theaters, studios, Jazz bars and live events.
 Power: 2000W Voltage : AC110-240v/50-60Hz
 Limiting Linsurance : 250V/5A Warm-up time : 1.5Min
 Fuel consumption : 100Min/L Drum capacity : 5 Ltr.
 The amount of smoke output : 10000Cu ft/M
 Electronic temperature control : support
 Adjust the amount of smoke size : supportDMX2
 Adjust the size of the wind : support DMX1
 Oil-free protection : support
 LCD controller : support LCD-2
 New Weight : 16 KG
 Gross Weight : 17.3 KG
 Dimensions : 56x43x31 CM

▶ Model No.: 11010006

FIRE MACHINE

The flame machine is suitable for any application that requires safe and dependable pyro effects. It can spew realistic flames from 1-2 meters and is meant for those climatic beat drop kinda moments.

Hexagon fire jet machine, DMX
 Power : 100 W
 Control : DMX512, electronic control
 Spray height : 1-2 M
 Voltage : AC 110V/220V 50/60Hz
 New Weight : 4.1 KG
 Gross Weight : 4.6 KG
 Cardboard packing (1in1)
 Dimensions: 23x23x51 CM



▶ Model No.: 11010007

FOG BUBBLE 1000

A kick ass gizmo that produces bubbles that are filled with fog.
 Power : 100 W
 Bubble max electric current : 5 A
 Power of fog : 900 W
 Fog max electric current : 10 A
 New Weight : 8.13 KG
 Gross Weight : 9.1 KG
 Cardboard packing (1in1)
 Dimensions : 59x31x35 CM

▶ Model No.: 11010008

FOG BUBBLE 2000

A kick ass gizmo that produces bubbles that are filled with fog.
 Power OF Bubble : 200 W
 Bubble max electric current : 5 A
 Power of fog : 900 W
 Fog max electric current : 10 A
 New Weight : 11.4 KG
 Gross Weight : 12.5KG
 Cardboard packing (1in1)
 Dimensions : 57x45x40.5 CM

▶ Model No.: 110100009

BUBBLE MINI

This machine is equipped with a handle to allow it to be hung while it shoots out colorless odorless bubbles that float down in the air at a slow pace creating a fairytale effect when combined with lighting effects.

Mini bubble machine, electric
 Power : 60 W
 Control mode : manual control
 Coverage : 60m²
 Wireless controller : optional
 Voltage : AC220V-230V 50/60Hz
 New Weight : 1.3 KG
 Gross Weight : 14.3 KG
 Cardboard packing (8in1)
 Dimensions: 53x53x50 CM

▶ Model No.: 11010010

BUBBLE BIG

It can blow continuous large quantities of bubbles that are colorless and odorless which diffuse light. It is suitable for mid to large sized applications.

Big Bubble machine
 Power : 300 W
 Control mode : wireless remote control/electronic control
 Coverage : 100m²
 Voltage : AC110-220V 50/60Hz
 New Weight : 9.34 KG
 Gross Weight: 11.56 KG
 Cardboard packing (1in1)
 Dimensions: 49x49x43 CM

▶ Model No.: 11010011

LED CONFETTI BLOWER

One of the highest selling mini confetti blowers in the world. It uses a fan for propulsion to shoot confetti up to 5M high. The compact easy to use device has 6pcs of Quad LEDs around the circumference that add color to the confetti in low light environments.

Max Height : 5M (20s)
 Power : 1500 W
 Control : DMX control, Wireless control
 LED lamp : 6pc RGBA 8W
 New Weight : 10 KG
 Gross Weight : 11 KG
 Cardboard packing (1in1)
 Dimensions : 39.5x30x55.5 CM

▶ Model No.: 11010012

CONFETTI CO2

CONFETTI CO2 is a professional stage effect confetti blaster. With an integrated case, simple outer case and easy assembling, you just need to open the cover and put the output tube in the right direction with a movable clock handle, in the same way, to pack it back when storage.

Max Height : 15M TO 18M
 Control : Manual control
 New Weight : 20 KG
 Gross Weight : 30 KG
 Cardboard packing (1in1)
 Dimensions : 67x38x126 CM



▶ Model No. : 11011001



DMX CONSOLE-1024

A standard DMX protocol control unit for 1024 channels with photoelectric isolation signal output.

Power : AC 100- 240V / 50-60Hz.
DMX Channels : 1024
Mating number of fixtures : 96
Control channels : Each Scanner 40 main channel + 40 trim
Fixture Library : R20 pearl light library support
The number of scenes that can be saved : 60
The number of scenes that can run simultaneously: 10
The total number of steps in a multi-step scenario: 600
Scene time control : fade in, fade out, LTP sliding
Graphics can be stored for each scene: 5
Faders scenes and dimming : Support
Graphics can be run at the same time the number : 10
Master Faders : Global, repeat, lighting
U disk read : Support FAT32 format
Net Weight : 8.3 KG Gross Weight : 16.3 KG
Flight case packaging (1in1) : 56X44X22 CM

▶ Model No. : 11011002



DMX CONSOLE - 2000

A standard DMX protocol control unit for 512 channels with photoelectric isolation signal output.

Power : AC 100- 240V / 50-60Hz.
DMX Channels : 512
Mating number of fixtures : 40
Control channels : Each scanner 36 main channel
The number of scenes that can be saved : 40
The number of scenes that can run simultaneously : 4
The total number of steps in a multi-step scenario : 40
Master Faders : Global, repeat, lighting
Net Weight : 3.7 KG
Gross Weight: 20 KG
Cardboard packing (5in1)
Package : 63X44X31 CM

▶ Model No.: 11011005



DMX CONSOLE GREAT 512

A standard DMX protocol control unit for 512 channels. It can be assigned as desired to control 32 soft patches for 28 fixtures with 18 control channels each. There is an in built USB port to store programming data. Quick and easy programming is possible thanks to 9 integrated movement patterns and 7 color effects. 32 programmable chases with 100 scenes each can be stores. Multiple options included with Manual control, time control, blackout, sound control and so on.

back light LCD
(2 x 16 characters), RDM support.
Net Weight : 1.89 KG
Gross Weight : 18 KG
Cardboard packing (10in1)
Package: 59X44X56 CM

▶ Model No.: 11011006



DMX CONSOLE 512

This unit can control 24 intelligent fixtures of up to 16 channels each. 30 banks of 8 programmable scenes and 6 programable chases of 240 scenes can be stored. There are multiple modes such as music mode, auto mode, MIDI control over banks, blackout and so on. There is an inbuilt storage for memory in case of power failure.

4 bit LED display
DMX in/out : 3 pin XRL
Power Supply : 90-240 Vac, 50-60Hz (DC9V-12V)
Power Consumption : 10W
Net Weight : 2.1 KG
Gross Weight : 24 KG
Cardboard packing (10in1)
Package : 52X45X54 CM

▶ Model No. : 11011003



DMX SPLITER 6CH ROUND

A truss mountable 6-way DMX splitter with independent power supply for all 6 output ports to run standard DMX 512 protocol.

Input : XLR-3-M
Output : XLR-3-F
RS-485
Political isolation of the input to the output: >AC300V
Net Weight : 0.9 KG
Gross Weight: 14 KG
Cardboard packing (10in1)
Package: 91X37X24 CM

▶ Model No. : 11011004



DMX SPLITER 8CH 2IN1

This unit has 2 inputs and 4 outputs with perfect electrical isolation between inputs and outputs. Furthermore, each of the DMX outputs are independently driven and isolated. Up to 32 units can run on each of the output connectors thus offering maximum functionality.

Power input : IEC connector on rear panel
Power input : AC120V-240V 50Hz/60Hz
Consumption : 20W
Net Weight : 2.4 KG
Gross Weight : 15.5 KG
Cardboard packing (5in1)
Package : 51X24X69 CM



▶ **Model No. : 11012006**



POWER DISTRIBUTOR 63A WITH FAULT CURRENT CRICKET

This modular power distribution rack has 12 CEE Norm output connectors of 16A. It is capable of 63A of input and output. Its IP44 rating makes it an ideal solution for outdoor event power distribution.

- Power Input : 5P 63A 380V~
- Net Weight : 21.95 KG
- Carton Size: 58x47.5x46 CM
- Gross Weight: 23.3 KG
- 12 x 3PIN 16A Output
- 1 x 5PIN 63A CEE Input & output
- Delixi breaker
- Voltage meter
- IP67 Cover to protect the breaker
- IP Rated : IP44
- Rain protection bag (optional)
- Wheel (optional)

POWER DIMMER

▶ **Model No. DK1216 : 11012005**

▶ **Model No. DK626 : 11012007**



NET.DO. DK1216/DK626 DIMMER PACK

Dk1216 12 channel digital dimmer, 16A per channel DMX512/1990 standard. Magnetic ring with a high anti-jamming, excellent anti-jamming capability of audio/ video almost no interference. Switch insurance, with over-current automatic shutdown protection. When DMX512 signal is broken off, every channel's output can be hold. High precision zero-crossing sampling, the output consistency of channels is better. 9 dimming curves: Every channel is chosen independently. Preheat adjustable to every channel. It can store 9 scenes that can be preset, manual dimming independently without any console. Power-down data retention, boot soft start to prevent the boot transient output.

Electrical automatically adapt the original frequency, range: 45 ~ 65Hz. LCD display with back light.
Power supply : Tri-phase or mono-phase operation : AC220V±10%, 45 ~ 65Hz.
Net Weight : 11.60 KG Gross Weight: 14.1 KG
Package: 56X56X22 CM , Cardboard packing (1in1)

CABLE TESTER

▶ **Model No. :11012010**



CABLE TESTER

AN easy to carry cable tester that can be used to check the most commonly used types of audio, video and lighting cables for continuity.

- 3&5-Pin XLR (M/F),
- RCA,
- 3&5&8-Pin Din,
- 4&8 -pole speakon,
- 4-Pin S type Jack,
- RJ45,
- USB(A-A)
- Powercon in/out
- Pin diagrams on facing
- 9V Battery Compartment (battery not included)

FLOOD LIGHT 400W

LED : OSRAM
LED COLOR : 3000K / 6500K
LENS ANGLE : 120°
MATERIAL : ALUMINUM



FLOOD LIGHT NANO 300W

LED : OSRAM
LED COLOR : 3000K / 6500K
LENS ANGLE : 120°
MATERIAL : ALUMINUM



FLOOD LIGHT NANO 200W

LED : OSRAM
LED COLOR : 3000K / 6500K
LENS ANGLE : 120°
MATERIAL : ALUMINUM



FLOOD LIGHT NANO 150W

LED : OSRAM
LED COLOR : 3000K / 6500K
LENS ANGLE : 120°
MATERIAL : ALUMINUM



FLOOD LIGHT NANO 100W

LED : OSRAM
LED COLOR : 3000K / 6500K
LENS ANGLE : 120°
MATERIAL : ALUMINUM



FLOOD LIGHT NANO 50W

LED : OSRAM
LED COLOR : 3000K / 6500K
LENS ANGLE : 120°
MATERIAL : ALUMINUM



Pixel Round Bulb Series



Pixel Square Bulb Series



Pixel Round Bulb Belt



Pixel Square Bulb Belt



Pixel Poster



Pixel Toran



Pixel Running Controller



Pixel MASTER Controller




LED BULB AC




LED BULB DC



CAP HOLDER



LED SERIES & BELT



VENI & CELLING BELT



SERIES WIRE



SERIES WIRE



NIWAR PATTI

